

Dido 60



M229 OA

Dido 61



M229 OG

Tellus 64




M246 OA

Type nr.		Citizen LED	
Photometric		Beam angle	
Type	code	Data	
M229 OA	C4130	20	
	C4230	32	C-01
	C4330	43	

Type nr.		Citizen LED	
Photometric		Beam angle	
Type	code	Data	
M229 OG	C0000	114°	C-01


Type nr.		Citizen LED	
Photometric		Beam angle	
Type	code	Data	
M246 OA	C4130	20°	
	C4230	32°	C-01
	C4330	43°	

Dido 60




M 229 OA

Dido 61



M 229 OG

Tellus 64



M 246 OS

## Add On

**UK** Methusalem fixtures made of aluminum, have the CLT label that guarantees the luminous flux, light color and lifespan.

**NL** Methusalem armaturen uit aluminium, voorzien van het CLT label dat garant staat voor behoud van lichtstroom, lichtkleur en levensduur.

**D** Methusalem leuchten aus alu. Designkühlkörper mit CLT-label. Dadurch wird der Lichtstrom, Lichtfarbe, und die Lebensdauer garantiert.

Design: Egbert Keen

Minos 79



M236 OA

Minos 99



M238 OA

Type nr.		Citizen LED	
Photometric		Beam angle	
Type	code	Data	
M236 OA	C4430	25°	C-03
	C4530	36°	
	C4630	50°	
<b>Xicato LED</b>			
	code	angle	Data
	XC 30	41°	X-03
	XD 30	56°	

Type nr.		Citizen LED	
Photometric		Beam angle	
Type	code	Data	
M238 OA	C0730	21°	C-04
	C0830	36°	
	C0930	56°	
	C1030	73°	
<b>Xicato LED</b>			
	code	angle	Data
	XE 30	21°	X-04
	XF30	40°	
	XG30	59°	

## DATA Matrix

Code	mA	Lm	Lm/W	Vf	W	K	CRI
C-01	350	386	121	9,1	3,2	3000	85
	500	524	110	9,5	4,7	3000	85
C-03	350	1577	126	35,6	12,5	3000	85
	500	2160	117	36,9	18,4	3000	85
X-03	350	1105	119	29,3	9,3	3000	85
	500	1490	110	30,0	13,6	3000	85
	700	2000	103	30,7	19,5	3000	85

Code	mA	Lm	Lm/W	Vf	W	K	CRI
C-04	350	1680	139	34,5	12,1	3000	85
	500	2331	131	35,5	17,7	3000	85
	700	3143	123	36,6	25,6	3000	85
X-04	500	1585	120	29,3	13,2	3000	85
	700	2100	111	29,8	18,9	3000	85
	1050	3000	103	30,7	29,3	3000	85

keen  
Lichtdesign

## Drivers pag. 58-61

RAL 9018


RAL 6034

RAL 7037

Special RAL


Methusalem

Minos 79



M 236 OS

Minos 99



M 238 OS

